Approved For Release 2001/07/16 : CIA-RDF 76-02820A000100080011-0

	The Files	18 September 1956
25X1A9a		
25X1A5a	Trip and Progress Repo	ort,
25X1A 25X1A5a	1. On 22 and 23 August 1 to determine the sta	1956, I visited the Plant in 25X1A5a1 stus of the tasks under the subject contract.
25X1A5a	a1	
	Order 1 concerns the miniature Branch and Task Order 2 concer Auxiliary Functions Branch. T however work on Task Order 4 h work on the "wrap-around" reco (300-25000 cps) version of the that much of the basic materia applicable to this unit. Part	of discussion were Task Orders 1 and 2. Task recorder being developed for ELINT Activities as the "break-down" recorder being developed for task Orders 4 and 5 were briefly mentioned, as not yet started. This concerns additional order. Task Order 5, the high frequency "break-down" recorder, has been started in 1 developed under Task Order 2 will be a and pieces are now being delivered by various of a unit which will eventually form the basis r 5.
5X1A5a1	available. The unit was operate recording appeared to be quite wow or flutter in the output. intelligibility of the spoken that the end of a track was hard reversal of the machine at the and I would not have been award itself click during this interfailings of the unit. The qualitationary the frequencies be considerable distortion evident to insufficient bias current at 2.1 mils and should be operated as at 2.1 mils and should be operated as a considerable distortion.	gineering model of the "break-down" recorder is ting with a full load of tape, and on voice satisfactory. There was little evidence of It was interesting to note that the loss of word during the reversal period of the machine ly noticeable. On a musical selection, the end of the track was not noticeable at all e of the change unless I had heard the machine wal. Other tests, however, revealed certain lity of recording a steady-state signal, elow 1000 cycles, is rather poor with indicated this was due primary cross the head. The present head is operating at 3.5 mils. This has necessitated a r and the work is not yet complete. It will

Approved For Release 2001/07/16 : CIA-RDP78-02820A000100080011-0

25X1A5a1 above 4000 cycles. Indicated that they would investigate this and

take necessary steps to correct it. The method devised for loading and removing the tape appears to be quite satisfactory with one end of the

sufficient drive. I noted also, that there appeared to be some distortion resulting from the signal beating with the bias oscillator at frequencies

magnetic tape being attached to a special plastic core. Loading is quite simple, with unloading hardly less simple, except that a small screw driver should be used to first free the plastic core from the reel. I suggested the use of a special flat tool for this. would make one and try it out. The recorder has recently undergone a series of cold-chamber tests with the self-contained batteries. The results of this will be tabulated and forwarded to us at a later date, however, the highlight of the test indicated that the recorder will operate satisfactory for a full 24-hour period at a minimum temperature of minus 40 Fahrenheit. Below this temperature the recorder continues to operate satisfactory but the batteries lose voltage and capacity. It became quite evident that the original schedule of 31 August will not be met. I discussed this problem at some 25X1A5a1 length with who explained that a number of factors effected this, not the least of which was a complete company re-organization early in the summer. The company management has now been stablized, and all other factors relating to this task have been largely resolved. One problem affecting delivery was the under estimation of the engineering time required for the amplifier. During the initial estimates, 360 hours of engineering time for the design had been assigned. At this date, more than 1200 hours have been spent designing the amplifier. Most of this was spent in trying to climinate the noise interference created by the motor. At the moment, everything seems satisfactory, and close inspection of the amplifier output on an oscilloscope showed no evidence of motor noise. I have reviewed the delivery schedules of the various parts and pieces which are being manufactured by outside suppliers and find that the latest delivery estimate is 6 October 1956. 25X1A5a1 themselves would be completed and tested prior to this time and that the only required work prior to shipment to us will be to install the units in the case. I pointed out that a letter from the company to the contracting officer will be required, indicating the new delivery schedule. I also requested at this time that all programs, Task Orders 1 through 5, be very closely reviewed and that if any change in time is necessary, to incorporate these in the same 25X1A5a1 letter. gave his assurance that this will be given their immediate ettention. 4. On Thursday morning, 23 August, accompanied by I visite25X1A5a1 the plant of 25X1A5a1 Vice-President. This trip was made for we met with 25X1A5a1 two reasons. I wished to observe the status of the motor which 25X1A5a1 is making under sub-contract to for the ministure 25X1A5a1 recorder, and secondly I wished to inspect the facilities of this plant as 25X1A5a1 they appear to have great capabilities in electro-mechanical equipments.

5. The motor design for the miniature recorder has been finalized and production of the motors is well under way. A drawing of this motor is attached. It will be noted that the armature consists of three flat coils attached to a commutator consisting of twelve segments. This will rotate in a ring magnet of 8 poles. The speed of rotation is relatively slow and the armature shaft will be the direct drive capstan for the tape. I was rather intrigued by the ring magnet and asked if his company had had 25X1A5a1 any difficulty in getting it. He admitted they had, and indicated that

Approved For Release 2001/07/16 : CIA-RDP76-02820A000100080011-0

25X1A5a1 25X1A5a1	and certain other companies had declined to make such a unit. then proceeded to make their own. The method of manufacture is rather unique, and to my knowledge has not been duplicated elsewhere. This
25X1A5a1	
05)/445 4	
25X1A5a1	6. Back at the ministure recorder at greater length and find that the solving of the motor problem has apparently removed the last major barrier in the design of this
25X1A5a1	recorder. assured me that earlier experiments have indicated that there will be no major problems in the production of the amplifier unit for the system nor for the production of a play-back unit to be used in connection with these units.
	7. We discussed briefly Task Order 5, the high frequency adaptation of the "break-down" recorder, but there is little information available, as the unit has not yet been built. The principal effort new being directed toward production of the items under Task 2.
25X1A5a1	8. In conclusion, the work at satisfactory although the delivery schedules are not being met. There is, however, considerable evidence that the situation is well in hand and that we can expect delivery of the items under Task 2 to be made by mid-October. The delivery of the miniature recorders under Task 1 will probably not be available before the later part of the year. I should also like to add that I was considerably impressed by the versatility and capability of the facilities available at the satisfaction of the ATP-3 printer and in all likelihood could make certain desirable improvements in the unit. I
25X1A5a1	also had in mind the work anticipated on repackagging and redesigning of the ET-2.
	A request has been made of the Security Division of Logistics to have
25X1A5a1	clearance renewed and transferred. 25X1A5a1

25X1A9a

Attachment:

Drawing of miniature motor

OC/E/R&D-EP/FCS:jac (18 September 1956)

cc: Monthly Report (2)
R&D Subject File
Lab

Approved For Release 2001/07/16 : CIA-RDP 2020A000100080011-0